



DC01x-2G Series Type D (LED) Emergency Back Up

Built-in Emergency Lighting — Bi-Level Lighting

- Housing: Die-formed cold-rolled steel / Epoxy powder coating
- Shade: High Transmission Glass Create Excellent Light Distribution and Uniformity
- LED: High Efficiency, High CRI, Binned and Mixed to Reach Uniform Light
- 5 Years warranty on Driver and LED Module
- Certification: ETL/cETL Listed

Emergency Backup Models

MODEL	INPUT VOLTAGE	INPUT WATTAGE	LED CT	- CRI-	LUMEN (TYP)	SIZE (OD X H)	ENERGY STAR
DC012D-2G-D-xxxxK-EM	120V	18W	3000K or 4000K	> 80	1340	11.8" x 4.5"	Yes
DC014D-2G-D-xxxxK-EM	120V ~ 277V	24W	3000K or 4000K	> 80	2000	14.5" x 5.0"	Yes
DC016D-2G-D-xxxxK-EM	120V ~ 277V	28W	3000K or 4000K	> 80	2300	16.0" x 5.4"	Yes
DC018D-2G-D-xxxxK-EM	120V ~ 277V	35W	3000K or 4000K	> 80	2800	17.8" x 5.4"	Yes

Bi-Level Lights - With Built-In High Frequency Sensor

MODEL	INPUT VOLTAGE	INPUT WATTAGE	LED CT	- CRI-	LUMEN (TYP)	SIZE (OD X H)	ENERGY STAR
DC012D-2G-D-xxxxK-Bi	120V	18W	3000K or 4000K	> 80	1340	11.8" x 4.5"	Yes
DC014D-2G-D-xxxxK-Bi	120V ~ 277V	24W	3000K or 4000K	> 80	2000	14.5" x 5.0"	Yes
DC016D-2G-D-xxxxK-Bi	120V ~ 277V	28W	3000K or 4000K	> 80	2300	16.0" x 5.4"	Yes
DC018D-2G-D-xxxxK-Bi	120V ~ 277V	35W	3000K or 4000K	> 80	2800	17.8" x 5.4"	Yes

Bi-Level Lights - With Emergency Back Up Lights

MODEL	INPUT VOLTAGE	INPUT WATTAGE	LED CT	- CRI-	LUMEN (TYP)	SIZE (OD X H)	ENERGY STAR
DC014D-2G-D-xxxxK-EM-Bi	120V ~ 277V	24W	4000K	> 80	2000	14.5" x 5.0"	Yes
DC016D-2G-D-xxxxK-EM-Bi	120V ~ 277V	28W	4000K	> 80	2300	16.0" x 5.4"	Yes
DC018D-2G-D-xxxxK-EM-Bi	120V ~ 277V	35W	4000K	> 80	2800	17.8" x 5.4"	Yes

• More Color Temperature Option: 3500K, 5000K